



## Material Properties and Dimensions



### Description

Western Excelsior manufactures a full line of Rolled Erosion Control Products (RECPs). Excel SR-1 temporary Erosion Control Blanket is composed of a 100% certified weed free agricultural straw matrix mechanically (stitch) bonded on two inch centers to a single synthetic, photodegradable net. The net is secured to the top of the RECP to restrain the straw matrix once installed. Excel SR-1 blanket is intended for use in channels or on slopes requiring erosion protection for a period up to twelve months. Actual field longevity is dependent on soil and climatic conditions.

### Specifications

Each roll of EXCEL SR-1 is manufactured under Western Excelsior's Quality Assurance Program to ensure a continuous distribution of fibers and consistent thickness. Verified values are provided in Table 1 and product characteristics are provided in Tables 2 and 3. Values provided in Tables 1, 2 and 3 represent expected values at the time of manufacture. Installation instructions and performance data are available from Western Excelsior's Technical Support Division.

Tested Property	Test Method	Value	Units
Tensile Strength	ASTM D6818	4.8 (MD), 4.8 (TD)	lb/in
Elongation	ASTM D6818	15 (MD), 20 (TD)	%
Mass per Unit Area	ASTM D6566	8.0	oz/yd <sup>2</sup>
Thickness	ASTM D1777	7.5	mm
Light Penetration	ECTC TASC 00197	15	% open
Water Absorption	ASTM D1117	425	%

Top Net	Synthetic Photo-degradable
Bottom Net	N/A
Top Net Opening	0.50" x 0.54" (Nominal)
Bottom Net Opening	N/A

Style	Narrow	Wide
Roll Width	7.5 ft	15.0 ft
Roll Length	120 ft	120 ft
Coverage	100 yd <sup>2</sup>	200 yd <sup>2</sup>
Roll Weight	55 lbs	110 lbs

Document # WE\_EXCEL\_SR1\_SPEC. This document has been developed to provide the characteristic properties of the product described. For questions, to request performance data or installation recommendations, contact Western Excelsior at 800-967-4009 or wexcotech@westernexcelsior.com. Updated 06/07.