Environmentally Friendly Surfacing





Available in





Green



Cypress







Tan



Redwood



Quick, Pour-in-Place Installation

- · Mixed on site and applied quickly in a single pour with minimal equipment
- · Made from recycled tires and is ADA compliant, every 1000 square feet of 2" thick Porous Pave™ keeps 4500 Lb of tires out of the landfill
- · Can be applied in temperatures between 40° and 90°F and generally cures in 24 hours
- · Allows larger volumes of water to pass through (approximately 6300 gallons per hour, per square foot) which reduces runoff by allowing water to soak through into the ground

Flexible & Durable

- · Slip resistant, flexible surface resists crumbling and cracking, reduces "trip and fall" accidents
- Resistant to oil, chlorine, ozone, UV rays, muratic acid, transmission fluid, gasoline, diesel, hydraulic fluid, salt water and many other hostile materials
- · Non-flammable and non-toxic

Many Applications

- Trails & Pathways
- · Parks Playgrounds
- Driveways
- · Patios & Decks
- · Tree Surrounds
- · Maintenance Strips
- · Concrete/Asphalt/Wood Overpours
- Pool Surrounds

Overpours

- · Can be installed in new construction or over top of existing concrete or wood decks
- Great traction when wet, reduces slip and fall accidents







