

PROJECT SUMMARY

Roadway

Lake Wales, FL

The Florida Department of Transportation (FDOT) needed to resurface six miles of State Route 60 in Polk County. For more than a decade, FDOT had installed similar roadway projects without a paving fabric, however it was disappointed with the lifetime performance of these resurfaced roads.

The spec for this project was open to all paving fabrics, but PETROMAT Plus-White was selected because its reflective properties increases visibility during night paving and remains up to 50 degrees cooler than dark paving fabric during daytime paving. Additionally, PETROMAT Plus-White's solar reflective fabric is designed to allow asphalt to cool faster and stay cooler during installation, thus minimizing tack oil bleed through and asphalt tracking.

Approximately 6,000 square yards of PETROMAT Plus-White was installed. Prior to installation, the road was milled. PETROMAT Plus-White can be placed directly on any milled surface without a leveling course. Once installed, it creates a stress absorbing interlayer that slows the progression of reflective cracking. When saturated with asphalt cement, PETROMAT Plus-White's performance is equal to an additional 1.5" of overlay thickness.



PROBLEM

FDOT needed to resurface six miles of State Route 60 due to cracking and fatigue



INSTALLATION

Approximately 6,000 square yards of PETROMAT Plus-White was installed to increase the lifetime performance of the roadway



The Cool, Track-less Paving Fabric

PropexGlobal.com/PetromatPlusWhite

FEATURES & BENEFITS

- Solar reflective fabric is designed to remain up to 50° F cooler than dark paving fabric once installed
- Prevents the time and cost of sanding to enable construction traffic without fabric damage
- Enables a cooler, safer work environment

- White fabric provides better visibility during nighttime paving
- Greatly extends the life of new asphalt concrete pavements and overlays
- Creates an effective moisture barrier to maintain the strength of pavement support layers



PERFORMANCE

Once installed, PETROMAT Plus-White's performance is equal to an additional 1.5" of overlaye thickness



INNOVATION TO BUILD ON™

Visit our website for more information, Product Samples, or other inquiries, or call Customer Service at 800 624

PO Box 19269 4019 Industry Drive Chattanooga, TN 34716 p: 800 621 1273 f: 423 899 5005 PropexGlobal.com

PGS-1635E-001 (02/2020)