

* Patent Pending

Specifications



Western Excelsior manufactures a full line of Rolled Erosion Control Products (RECPs). Tackmat_x Rapid Go temporary Erosion Control Blanket is composed of a 100% machine produced High Altitude Rocky Mountain Aspen Excelsior matrix mechanically (stitch) bonded on two inch centers to a single photodegradable, synthetic net. The excelsior matrix consists of curled, machine produced fibers with greater than eighty percent longer than six inches. Tackmat_x Rapid Go is treated with a erosion control performance enhancing polyacrylamide. When installed, the polyacrylamide is deployed to the soil surface and the interaction of treated soil and excelsior fibers provides enhanced erosion control. Tackmat_x Rapid Go is available in natural color or dyed green and recommended for use in channels or slopes requiring erosion protection for a period up to fifteen months. Actual field longevity is dependent on soil and climatic conditions.

Each roll of Tackmat_x Rapid Go is made in the USA and manufactured under Western Excelsior's Quality Assurance Program to ensure a continuous distribution of fibers and consistent thickness. Typical manufactured properites are provided in Table 1 and product characteristics are provided in Table 2.

Tested Property	Test Method	Value
Tensile Strength (MD) x (TD)	ASTM D6818	5.0 lb/in (0.9 kN/m) x 4.0 lb/in (0.7 kN/m)
Elongation (MD) x (TD)	ASTM D6818	12 % x 10 %
Mass Per Unit Area	ASTM D6475	8.0 oz/yd^2 (271 g/m^2)
Thickness	ASTM D6525	0.35 in (9 mm)
Light Penetration	ASTM D6567	35 % open
Water Absorption	ASTM D1117	250 %

Table 1- Specified Expected Values

Table 2 - Netting

Top Net Type	Synthetic, Rapid Photodegradable
Bottom Net Type	N/A
Top Net Opening Dimensions	0.8 in (20 mm) x 1.0 in (25 mm)
Bottom Net Opening Dimensions	N/A

Tackmat_x Rapid Go is available in multiple roll sizes ranging in width from 4.0 ft to 16.0 ft. and 45 ft to 600 ft in length. Standard roll sizes are 80 square yards, measuring 4.0 ft wide by 180.0 ft long or 8.0 ft wide by 90 ft long. Custom roll sizes are available upon request.

Document # WE_EXCEL_TMxRG_SPEC. This document has been developed to provide the characteristic properties of the product described. For questions, to request performance data or installation recommendations, contact Western Excelsior at 866-540-9810 or wexcotech@westernexcelsior.com. Updated 4/14/2014.