



Terra-Wood™

MSDS Number: CON005

Revision Date: 1/1/14

Page 1 of 5

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC
750 LAKE COOK ROAD
SUITE 440
BUFFALO GROVE, IL 60089

Phone: (847) 215-1144
Fax: (847) 215-0577
Email: profileproducts.com
Web: www.profileproducts.com

Product Name: Terra-Wood™
Revision Date: 1/1/14
MSDS Number: CON005
CAS Number: Not applicable
Product Use: Erosion control and revegetation mulch for hydraulic seeding

Product Description: Green dyed wood fibers

2 HAZARDS IDENTIFICATION

- Route of Entry:** Inhalation, skin contact, eye contact
- Inhalation:** Wood dust may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.
- Skin Contact:** Wood dust can cause irritation. Skin absorption is not known to occur.
- Eye Contact:** Wood dust can irritate the eyes.
- Ingestion:** No reports of human ingestion.

NFPA: Health = 1, Fire = 1, Reactivity = 0



OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200



Terra-Wood™

MSDS Number: CON005

Revision Date: 1/1/14

Page 2 of 5

3	COMPOSITION/INFORMATION ON INGREDIENTS
---	---

Ingredients:

Cas #	Perc.	Chemical Name

4	FIRST AID MEASURES
---	---------------------------

Inhalation: Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.

Skin Contact: Usually not a problem. Wash off with running water if irritation is experienced.

Eye Contact: Open eyelids and flush with water.

Ingestion: Get medical attention.

5	FIRE FIGHTING MEASURES
---	-------------------------------

Flammability: Combustible product

Flash Point: Not applicable

Flash Point Method: Not applicable

Autoignition Temp: 200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

6	ACCIDENTAL RELEASE MEASURES
---	------------------------------------

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7	HANDLING AND STORAGE
---	-----------------------------

Handling Precautions: Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.

Storage Requirements: Store in a cool, dry place. Keep away from sources of ignition.



Terra-Wood™

MSDS Number: CON005

Revision Date: 1/1/14

Page 3 of 5

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling operations.
Personal Protective Equip: Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.
Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.
Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.
Footwear: The product is slippery when wet. Wear appropriate footwear.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dyed, green wood fibers - Pine and mixed hardwoods
Physical State: Wood Fibers
Spec Grav./Density: Lighter than water
Vapor Pressure: N/A
Odor: Mild wood odor

10 STABILITY AND REACTIVITY

Stability: Stable product
Conditions to Avoid: Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).
Materials to Avoid: Strong acids and oxidizers
Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.
Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Occupational Exposure Limits:

Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m³ (Inhalable fraction); A4

Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust); 5 mg/m³ (Respirable fraction)

Irritancy: Wood dust is a mild irritant

Sensitization: Some wood dusts may cause allergic skin reactions



Terra-Wood™

MSDS Number: CON005

Revision Date: 1/1/14

Page 4 of 5

12 ECOLOGICAL INFORMATION

48-hr LC₅₀ = >100% for Daphnia magna when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

13 DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14 TRANSPORT INFORMATION

DOT Class: Not regulated #

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHA WAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance
CSWS = Clean Water Act Hazardous substances
EHS302 = Extremely Hazardous Substance
EPCRAWPC = EPCRA Water Priority Chemicals
HAP = Hazardous Air Pollutants
NJEHS = NJ Extraordinarily Hazardous Substances
NJHS = NJ Right-to-Know Hazardous Substances
OSHA PSM = OSHA Chemicals Requiring process safety management
SARA313 = SARA 313 Title III Toxic Chemicals



Solutions for your Environment™

GHS Safety Data Sheet

PROFILE Products, LLC

Terra-Wood™

MSDS Number: CON005

Revision Date: 1/1/14

Page 5 of 5

16

OTHER INFORMATION